

Technical Information Sheet



Metal Batten Strip

Packaging	Part Number
50 pieces of 3.05m per cardboard tube (152.4m)	W56RAC3053

Description

The Elevate™ Metal Batten Strips are designed for the mechanical attachment of the Elevate membrane and flashing details as per Elevate specifications and details.

Application

Metal Batten Strip can be applied in following Elevate systems: RubberGard™ EPDM, UltraPly™ TPO, GeoGard™ EPDM and PondGard™ EPDM.

Preparation

All cut edges of metal batten strips must be rounded and filed to remove burrs and sharp edges. Remove any shavings from the installation area.

Method of Application

Layout the Metal Batten Strips as specified and attach them to the substrate using the appropriate Elevate fasteners. To avoid buckling of the strip it is recommended to start at one end of the batten strip and fasten towards the other end and to install all fasteners at proper depth. Set the fastener head flush with the strip. Do not overdrive or underdrive the fastener. Adjoining strips need to overlap and are to be fastened using one single fastener in the overlapping hole.

Coverage

In compliance with wind design requirements and as per Elevate Technical Guidelines.

Characteristics

Technical	
• Material	Galvalume® AZ55
• Length	Strip of 3.05 m
• Width	25.4 mm
• Thickness	1.1 mm/ 1.2 mm
• Holes	diam. 8.7 mm at 152 mm o.c.

Storage

Dry and clean in original unopened packaging protected from the weather.

Shelf Life

Unlimited, if stored in the above-mentioned conditions.

Note:

This document is meant only to highlight Elevate products and specifications based on latest knowledge and experience and is subject to change without notice. Above mentioned values are based on tested samples and may vary within applicable tolerances. For latest and complete product and detail information, please refer to the technical information posted on www.holcimelevate.com. Holcim Solutions and Products EMEA BV ("Holcim") takes responsibility for furnishing quality materials which meet Holcim's published product specifications. As neither Holcim itself nor its representatives practice architecture, Holcim offers no opinion on and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. The selection of the appropriate product and its correct application is the responsibility of the customer and not of Holcim. No Holcim Representative is authorized to vary this disclaimer.