

Technical Information Sheet

QuickSeam™ Splice Tape

Packaging	Part Number
76 mm x 30.50 m per roll, 6 rolls per carton	W56RAC1603
152 mm x 30.50 m per roll, 2 rolls per carton	W56RAC1626

Note: Not all part numbers are available in each application. Includes scrubber handle and pads (quantity and type subject to change without notice).

Description

The Elevate™ QuickSeam Splice Tape 76 mm (3") and 152 mm (6") wide is designed for field splicing Elevate EPDM membrane panels.

Application

QuickSeam Splice Tape can be applied in following Elevate system(s): RubberGard™ EPDM, GeoGard™ EPDM, PondGard™ EPDM and GeoSmart™ EPDM.

Preparation

The Elevate EPDM surfaces must be prepared with QuickPrime™ primer, using a QuickScrubber™ tool. Use of other products is not allowed. Restore the tape to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

Method of Application

The 76 mm (3") wide tape is used for splicing standard seams without mechanical attachment in the seam. The 152 mm (6") wide tape is used for splicing seams with mechanical attachment centered within the seam. Refer to the Elevate technical guidelines for specific installation instructions.

Coverage

In accordance with length of seam. Adjoining QuickSeam Splice Tapes require an overlap of 25 mm and a QuickSeam FormFlash cover patch.

Characteristics

Technical	
• Base	Rubber polymers
• Color	Black
• Solvents	None
• Solids	100%
• State	Cured
• Thickness	0.6 mm ± 0.1 mm

Storage

Store in original unopened containers at temperatures between 15°C and 25°C, in a well-ventilated place. Keep the material dry and out of direct sunlight until ready for application.

Shelf Life

12 months can be expected if stored in above-mentioned conditions. Verify production date on each roll. Shelf life will be reduced if exposed to higher temperatures. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories.

Precautions

Refer to Safety Data Sheet.

Note:

This document is meant only to highlight Elevate products and specifications based on latest knowledge and experience and is subject to change without notice. Above mentioned values are based on tested samples and may vary within applicable tolerances. For latest and complete product and detail information, please refer to the technical information posted on www.holcimelevate.com. Holcim Solutions and Products EMEA BV ("Holcim") takes responsibility for furnishing quality materials which meet Holcim's published product specifications. As neither Holcim itself nor its representatives practice architecture, Holcim offers no opinion on and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. The selection of the appropriate product and its correct application is the responsibility of the customer and not of Holcim. No Holcim Representative is authorized to vary this disclaimer.